



ALBERT-LUDWIGS-
UNIVERSITÄT FREIBURG


Algorithms for Radio Networks

Routing, Flooding, DSR

University of Freiburg
Technical Faculty
Computer Networks and Telematics
Christian Schindelhauer



Protocols of the Internet

Application	Telnet, FTP, HTTP, SMTP (E-Mail), ...
Transport	TCP (Transmission Control Protocol) UDP (User Datagram Protocol)
Network	IP (Internet Protocol) + ICMP (Internet Control Message Protocol) + IGMP (Internet Group Management Protocol) 
Host-to-Network	LAN (e.g. Ethernet, Token Ring etc.)

TCP/IP Layers

▶ 1. Host-to-Network

- Not specified, depends on the local network, e.g. Ethernet, WLAN 802.11, PPP, DSL

▶ 2. Routing Layer/Network Layer (IP - Internet Protocol)

- Defined packet format and protocol
- Routing
- Forwarding


▶ 3. Transport Layer

- TCP (Transmission Control Protocol)
 - Reliable, connection-oriented transmission
 - Fragmentation, Flow Control, Multiplexing
- UDP (User Datagram Protocol)
 - hands packets over to IP
 - unreliable, no flow control

▶ 4. Application Layer

- Services such as TELNET, FTP, SMTP, HTTP, NNTP (for DNS), ...

Example: Routing between LANs



Routing Tables and Packet Forwarding

► IP Routing Table

- contains for each destination the address of the next gateway
- destination: host computer or sub-network
- default gateway

► Packet Forwarding

- IP packet (datagram) contains start IP address and destination IP address
 - if destination = my address then hand over to higher layer
 - if destination in routing table then forward packet to corresponding gateway
 - if destination IP subnet in routing table then forward packet to corresponding gateway
 - otherwise, use the default gateway

IP Packet Forwarding

- ▶ **IP -Packet (datagram) contains...**
 - TTL (Time-to-Live): Hop count limit
 - Start IP Address
 - Destination IP Address
- ▶ **Packet Handling**
 - Reduce TTL (Time to Live) by 1
 - If $TTL \neq 0$ then forward packet according to routing table
 - If $TTL = 0$ or forwarding error (buffer full etc.):
 - delete packet
 - if packet is not an ICMP Packet then
 - * send ICMP Packet with
 - start = current IP Address
 - destination = original start IP Address

Static and Dynamic Routing

► Static Routing


- Routing table created manually
- used in small LANs

► Dynamic Routing

- Routing table created by Routing Algorithm
- Centralized, e.g. Link State
 - Router knows the complete network topology
- Decentralized, e.g. Distance Vector
 - Router knows gateways in its local neighborhood

Intra-AS Routing

- **Routing Information Protocol (RIP)**
 - Distance Vector Algorithmus
 - Metric = hop count
 - exchange of distance vectors (by UDP)
- **Interior Gateway Routing Protocol (IGRP)**
 - successor of RIP
 - different routing metrics (delay, bandwidth)
- **Open Shortest Path First (OSPF)**
 - Link State Routing (every router knows the topology)
 - Route calculation by Dijkstra's shortest path algorithm



Distance Vector Routing Protocol

shortest path

► Distance Table data structure

- Each node has a
 - Line for each possible destination
 - Column for any direct neighbors

► Distributed algorithm


- each node communicates only with its neighbors

► Asynchronous operation

- Nodes do not need to exchange information in each round

► Self-terminating

- exchange unless no update is available




Distance Table for A

		via		Routing Table entry
from A		B	E	
to B		2	15	B ←
C		3	14	B
D		7	10	B
E		8	9	E ←

Distance Table for C


		via			Routing Table entry
from C		B	D	E	
to A		3	11	18	B
B		1	9	21	B
D		6	4	11	D
E		7	5	10	D

Distance Vector Routing Example



from A to	via		entry
	B	C	
B	1	8	B
C	6	3	C
D	2	9	B
E	7	4	C

Distance Vector Routing



from A to	via		entry
	B	C	
B	1	∞ -	B
C	∞ -	3	C
D	-	-	-
E	-	-	-

from B to	via			entry
	A	C	D	
A	1	-	-	A
C	-	3	-	C
D	-	-	1	C
E	-	-	8	D

from C to	via			entry
	A	B	E	
A	3	-	-	A
B	-	5	-	B
D	-	-	8	E
E	-	-	1	E

Distance Vector Routing




from B to	via			Entry
	A	C	D	
A	1	-	-	A
C	-	5	-	C
D	-	-	1	D
E	-	-	8	D

from C to	via			Entry
	A	B	E	
A	3	-	-	A
B	-	5	-	B
D	-	-	8	E
E	-	-	1	E

from B to	via			Entry
	A	C	D	
A	1	8	-	A
C	-	5	-	C
D	-	13	1	D
E	-	6	8	C

from C to	via			Entry
	A	B	E	
A	3	6	-	A
B	-	5	-	B
D	-	6	8	B
E	-	13	1	E



“Count to Infinity” - Problem


- ▶ Good news travels fast
 - A new connection is quickly at hand
- ▶ Bad news travels slowly
 - Connection fails
 - Neighbors increase their distance mutually
 - "Count to Infinity" Problem

“Count to Infinity” - Problem

Handwritten notes:
 $A \rightarrow B \rightarrow C$
 $B \rightarrow C$
 $A \rightarrow C$

Handwritten routing table for node B:

		via	
		A	C
to A		2	4
to C		5	1



from A			via B	Routing Table entry	from B			via A C	Routing Table entry
to	B		2	B	to	A	2	-	A
	C		3	B		C	5	-	A

from A			via B	Routing Table entry	from B			via A C	Routing Table entry
to	B		2	B	to	A	2	-	A
	C		7	B		C	5	-	A

from A			via B	Routing Table entry	from B			via A C	Routing Table entry
to	B		2	B	to	A	2	-	A
	C		7	B		C	9	-	A

Link-State Protocol

▶ Link state routers



- exchange information using Link State Packets (LSP)
- each node uses shortest path algorithm to compute the routing table

▶ LSP contains

- ID of the node generating the packet
- Cost of this node to any direct neighbors
- Sequence-no. (SEQNO)
- TTL field for that field (time to live)

▶ Reliable flooding (Reliable Flooding)

- current LSP of each node are stored
- Forward of LSP to all neighbors
 - except to be node where it has been received from
- Periodically creation of new LSPs
 - with increasing SEQNO
- Decrement TTL when LSPs are forwarded



Characteristics of routing in mobile ad hoc networks

► Movement of participants

- Reconnecting and loss of connection is more common than in other wireless networks
- Especially at high speed

► **Other performance criteria**

- Route stability in the face of mobility
- energy consumption




Unicast Routing

↪ Point to Point

0.5 → 0

Convergence cast




► Variety of protocols

- Adaptations and new developments


► No protocol dominates the other in all situations

- Solution: Adaptive protocols?

Multicast



Broadcast



Routing in MANETs

► Routing

- Determination of message paths
- Transport of data

► Protocol types

- ◉ proactive ↵
 - Routing tables with updates
- ◉ reactive ↵
 - repair~~m~~ of message paths only when necessary
- ◉ hybrid
 - combination of proactive and reactive

Routing Protocols

► Proactive

- Routes are **demand independent**
- Standard Link-State und Distance-Vector Protocols
 - Destination Sequenced Distance Vector (**DSDV**)
 - Optimized Link State Routing (**OLSR**)

► Reactive

- Route are determined when needed
 - Dynamic Source Routing (**DSR**)
 - Ad hoc On-demand Distance Vector (**AODV**)
 - Dynamic MANET On-demand Routing Protocol *Dymo*
 - Temporally Ordered Routing Algorithm (**TORA**)

► Hybrid

- combination of reactive und proactive
 - Zone Routing Protocol (**ZRP**)
 - Greedy Perimeter Stateless Routing (**GPSR**)

many more

Source Route

Trade-Off

- ▶ **Latency~~cy~~ because of route discovery**
 - Proactive protocols are faster
 - Reactive protocols need to find routes
- ▶ **Overhead of Route discovery and maintenance**
 - Reactive protocols have smaller overhead (number of messages)
 - Proactive protocols may have larger complexity
- ▶ **Traffic-Pattern and mobility**
 - decides which type of protocol is more efficient

Flooding

► Algorithm


- Sender S broadcasts data packet to all neighbors
- Each node receiving a new packet
 - broadcasts this packet
 - if it is not the receiver

► Sequence numbers


- identifies messages to prevent duplicates

► Packet always reaches the target


- if possible



Flooding Example




Flooding for Data Delivery




Packet for Receiver F

Flooding for Data Delivery




Flooding for Data Delivery

Receiver F gets packet and stops



Nodes G, H, I do not receive the packet



Flooding

► Advantage

- simple and robust
- the best approach for short packet lengths, small number of participants in highly mobile networks with light traffic

► Disadvantage

- High overhead
- Broadcasting is unreliable
 - lack of acknowledgements
 - hidden, exposed terminals lead to data loss or delay

Flooding

- ▶ **Produces too many unnecessary (long) data packets**
 - in the worst case, each participant sends each packet
 - many long transmissions collisions lead to long waiting times in the medium access
- ▶ **Better approach:**
 - Use of control packets for route determination
 - Flooding of control packet leads to DSR

Dynamic Source Routing (DSR)


► Johnson, Maltz

- *Dynamic Source Routing in Ad Hoc Wireless Networks*, Mobile Computing, 1996


► Algorithm

- Sender initiates route discovery by flooding of Route-Request (RREQ)-packets
 - Each forwarding node appends his ID to the RREQ-packet
- The receiver generates the routing information from the RREQ packet by producing a Route-Reply (RREP)-packet
 - using the route information of the packet is sent back to the sender
- Transmitter sends data packet along with route information to the receiver


DSR Example




DSR Example




DSR Example




DSR Example




DSR Example




DSR Example



DSR Example



DSR Example



Requirements

‣ Route Reply

- requires bidirectional connections
- unidirectional links
 - must be tested for symmetry
 - or Route-Reply must trigger its own route-request

‣ Data packet has all the routing information in the header

- hence: Source-Routing

‣ Route determination

- if no valid route is known

DSR Extensions and Modifications


- ▶ **Intermediate nodes can cache information RREP**
 - Problem: stale information
- ▶ **Listening to control messages**
 - can help to identify the topology
- ▶ **Random delays for answers**
 - To prevent many RREP-packets (Reply-Storm)
 - if many nodes know the answer (not for media access)
- ▶ **Repair**
 - If an error is detected then usually: route recalculation
 - Instead: a local change of the source route
- ▶ **Cache Management**
 - Mechanisms for the deletion of outdated cache information

DSR Optimization


Route Caching

- ▶ **Each node stores information from all available**
 - Header of data packets
 - Route Request
 - Route-Reply
 - partial paths
- ▶ **From this information, a route reply is generated**


DSR Route Caching




DSR Route Caching



DSR Route Caching



DSR Route Caching




DSR Optimization

Route Caching

- ▶ **If any information is incorrect**
 - because a route no longer exists
 - then this path is deleted from the cache
 - alternative paths are used
 - or RREQ is generated
- ▶ **Missing links are distributed by (RERR) packets in the network**

Route Error



DSR Discussion

► Benefits

- Routes are maintained only between communicating nodes
- Route caching reduces route search
- Caches help many alternative routes to find

► Disadvantages

- Header size grows with distance
- Network may be flooded with route requests
- Route-Reply-Storm
- Outdated information may cause cache overhead

AODV

► Perkins, Royer

- Ad hoc On-Demand Distance Vector Routing, IEEE Workshop on Mobile Computing Systems and Applications, 1999

► ~~Reaktives Routing-Protokoll~~

► Reactive routing protocol

- Improvement of DSR D
- no source routing
- Distance Vector Tables
 - but only for nodes with demand
- Sequence number to help identify outdated cache info
- Nodes know the origin of a packet and update the routing table


AODV

► Algorithm


- Route Request (RREQ) like in DSR
- Intermediate nodes set a reverse pointer towards the sender
- If the target is reached, a Route Reply (RREP) is sent
- Route Reply follow the pointers

► Assumption: symmetric connections

AODV: Example




AODV: Example




AODV: Example

A	via A
S	A
2	-
:	-
:	-
:	-




AODV: Example




AODV: Example

\neq via
S/E




AODV: Example


Handwritten red notes:

$$\begin{array}{c|c} \overline{E} & * \\ \hline S & A \\ \hline \overline{F} & \overline{F} \end{array}$$


AODV: Example




AODV: Example



AODV: Example

Data Packet[F]



Route Reply in AODV

► Intermediate nodes

- may send route-reply packets, if their cache information is up-to-date

► Destination Sequence Numbers


- measure the up-to-dateness of the route information
- AODV uses cached information less frequently than DSR
- A new route request generates a greater destination sequence number
- Intermediate nodes with a smaller sequence number may not generate a route reply (RREP) packets

Timeouts


- ▶ Reverse pointers are deleted after a certain time
 - RREP timeout allows the transmitter to go back
- ▶ Routing table information to be deleted
 - if they have not been used for some time
 - Then a new RREQ is triggered

Link Failure Reporting

- ▶ **Neighbors of a node X are active,**
 - if the routing table cache are not deleted
- ▶ **If a link of the routing table is interrupted,**
 - then all active neighbors are informed
- ▶ **Link failures are distributed by Route Error (RERR) packets to the sender**
 - also update the Destination Sequence Numbers
 - This creates new route request



AODV: Example



Detection of Link Failure

↪ proactive

▶ Hello messages


- neighboring nodes periodically exchange hello packets from
- Absence of this message indicates link failure

▶ **Alternative**


- use information from MAC protocol

Sequence Numbers

- ▶ **When a node receives a message with destination sequence number N**
 - then this node sets its number to N
 - if it was smaller before
- ▶ **In order to prevent loops**
 - If A has not noticed the loss of link (C, D)
 - (for example, RERR is lost)
 - If C sends a RREQ
 - on path C-E-A
 - Without sequence numbers, a loop will be constructed
 - since A "knows" a path to D, this results in a loop (for instance, CEABC)



Sequence Numbers






Optimization


Expanding Ring Search

- ▶ **Route Requests**
 - *start with small time-to-live value (TTL)*
 - if no Route Reply (RREP) is received, the value is increased by a constant factor and resent
- ▶ **This optimization is also applicable for DSR**

Relax



Bellman Ford



negative cost cycle

$$A \rightarrow C : -10$$



$$A \rightarrow B : 2$$



$$B \rightarrow A : \cancel{X} -8$$

$$B \rightarrow C : \cancel{X} -6$$

$$C \rightarrow A : -10$$

$$C \rightarrow B : \cancel{X} -4$$





SOURCE ROUTING

